



DIGITAL MONOCHROME SYSTEMS

PG

L2645, L2650, L2655

Securing a Good Impression in the Office



- SPEED
- ECO-FRIENDLY
- COMPACTNESS
- SAFETY
- QUALITY
- WI-FI AND WI-FI DIRECT *

* optional

Today's offices expect their print equipment to work efficiently and quietly and the **PG L2645, PG L2650 and PG L2655** have been designed to perform print tasks with the same excellence in productivity and reliability, as their predecessors, but now they can hardly be seen and are barely heard.

The trio of A4 mono PG L laser printers have been designed to blend in, with their all-cream coloured exterior, but still enable print-outs to be seen on the dark coloured paper-out tray, ensuring that no confidential prints can be left behind, as part of their standard security measures.

On the subject of security these printers have an enormous advantage over previous models: they all have a **standard Data Security Kit**, which, until now has been an optional extra, enabling the activation of data encryption and overwrite deletion functions.

In addition, users will benefit from reduced cost of ownership and improved care for the environment, through a reduced footprint, new eco-friendly packaging and very low energy consumption.

Meanwhile, the first print-out time is quicker, printing in A5 format is faster and banner printing has been designed to be much more convenient than previous models.



SPEED AND PRODUCTIVITY

LOW ENERGY CONSUMPTION

RESOLUTION IN PRINT UP TO 1200X1200 DPI

FAST FIRST PRINT-OUT TIME

SUPPORTS MOBILE PRINTING AND WI-FI

HIGH LEVELS OF DATA SECURITY AS STANDARD



Compact dimensions with a clean-cut finish



Control panel and display



PG L2655 configured with 4 x PF3110 Paper Trays

TECHNICAL SPECIFICATIONS

	PG L2645	PG L2650	PG L2655
GENERAL			
Type		Desktop Printer	
Technology		Monochrome Laser	
Control Panel		5-row LCD with alphanumeric keypad, rear-lit	
Print Speed, A4	Up to 45 ppm	Up to 50 ppm	Up to 55 ppm
Print Speed, A5	Up to 62 ppm	Up to 74 ppm	Up to 82 ppm
Print Resolution		1200 x 1200 dpi	
Warm-up Time	15 sec approx or less	20 sec approx or less	25 sec approx or less
First Print Out Time	5.3 sec or less	5.4 sec or less	4.5 sec or less
Dimensions (W x D x H)	380 x 410 x 285 mm		380 x 410 x 320 mm
Maximum Dimensions (W x D x H)	388 x 410 x 308 mm		388 x 410 x 343 mm
Basic Unit Weight	15 kg		16 kg
Power Consumption	AC 220/240 V, 50/60 Hz		
Product Code	B3798	B3799	B3800
PAPER HANDLING			
Input Paper Capacity	100-sheet multi-purpose tray; 60 – 220 g/m ² ; A4, A5, A6, Letter, Legal, Custom (70 x 148 – 216 x 356 mm, Banner paper up to 915 mm); 500-sheet multi-purpose paper tray, 60 – 120 g/m ² ; A4, A6, Letter, Legal, Custom (140 x 210 – 216 x 356 mm); Max. input capacity inc. options: 2,600 sheets	100-sheet multi-purpose tray; 60 – 220 g/m ² ; A4, A5, A6, Letter, Legal, Custom (70 x 148 – 216 x 356 mm, Banner paper up to 915 mm); 500-sheet multi-purpose paper tray, 60 – 120 g/m ² ; A4, A6, Letter, Legal, Custom (105 x 148 – 216 x 356 mm); Max. input capacity inc. options: 2,600 sheets	
Duplex Printing		Standard front-back mode	
Output Paper Capacity	Max 250 sheets face down for sensor full	Max 500 sheets face down for full page scan, 250 sheets face up with optional PT-320	
CONTROLLER			
Processor		ARM Cortex-A9/INA/1.2 GHz	
Memory		512 MB, Max 2.5 GB	
Standard Interface		USB 2.0 (Hi-Speed), 2 USB Host interfaces, Gigabit Ethernet (10/100/1000 baseT), Slot for optional print server or SSD hard disk, slot for optional SD/SDHC	
Emulations		PCL6 (PCL-XL, PCL5e), KPDL3, XPS, Open XPS, TIFF/JPEG, IBM Proprinter, LQ-850, LinePrint.	
Operating Systems		All current Windows operating systems, Mac OS X 10.9 or later, UNIX LINUX and other operating systems on request.	
Fonts/Barcodes		93 scalable fonts (PCL6/KPDL3), 8 fonts (Windows), 1 Bitmap font, 45 one-dimensional barcode types, 1 two-dimensional barcode type (PDF417); other barcodes available on request.	
Security Features		PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, Ipsec, SNMPv3, Encrypted PDF Direct Print	
Mobile Printing Mode		Olivetti Mobile Print app for IOS and Android; Airprint	
CONSUMABLES			
Black Toner Cartridge (B1228)		Up to 12,500 A4 pages. Initial supply up to 6,000 A4 pages	
Black Toner Cartridge (B1229)	N/A	Up to 15,500 A4 pages. Initial supply up to 8,000 A4 pages	
Black Toner Cartridge (B1230)	N/A	N/A	Up to 15,500 A4 pages.
Maintenance Kit (B1287)	Up to 300,000 A4 pages.	N/A	Initial supply up to 8,000 A4 pages
Maintenance Kit (B1376)	N/A		N/A
			Up to 500,000 A4 pages.
OPTIONS			
PF-3110 Tray, max 4 (B3637)	500 sheets; 60-120 g/m ² ; A4, A5, B5, Letter, Legal, Custom (92 x 162 mm - 216 x 356 mm)		
PF-3100 Large Capacity Tray (B3404) + PB-325 Support Base (B4367)	Max 2,000 sheets, 60-220 g/m ² (76 x 148 mm - 216 x 305 mm); not compatible with PF-3110		
PT-320 (B4365) Paper Output Tray	N/A	Thinprint support	Up to 250 sheets face-up
UG-33 (B8403)			
Memory expansions			
- MD3-1024 (B3472)		1.024 MB	
- MDDR3-2GB (B3519)		2.048 MB	
- HD-6 Hard Disk SSD (B4369)		32 GB for simplified document management	
- HD-7 Hard Disk SSD (B4844)		128 GB for simplified document management	
Optional Interfaces			
- IB-32B (B3405)		IEEE1284 parallel interface	
- IB-50 (B4805)		Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ45)	
- IB-51 (B4933)		Wireless network (802.11b/g/n)	
- IB-36 (B3406)		Wireless network (802.11b/g/n) with Wi-Fi Direct	